

WYKAZ STALI ZBROJENIOWEJ NR 4 DO RYS. 14/K

RODZAJ I LICZBA PRĘTÓW ZBROJENIA												
NAZWA	ILOŚĆ SZT.	NR PRĘTA	ŚRED. PRĘTA mm	GATU- NEK	DŁUGOŚĆ m	LICZBA W 1 EL. SZT.	LICZBA OGÓLNA SZT.	DŁUGOŚĆ ŁĄCZNA				
								B240		B500		
								# 6 m	# 8 m	# 12 m	# 16 m	
FS-1	8	1	12	B500	2,57	8	64				164,48	
		2	12	B500	2,14	17	136				291,04	
		3	12	B500	2,64	11	88				232,32	
		4	12	B500	1,51	10	80				120,80	
		5	8	B500	1,66	20	160			265,60		
		6	8	B500	1,18	10	80			94,40		
FS-2	5	1	16	B500	2,81	12	60					168,60
		2	12	B500	2,14	6	30				64,20	
		3	12	B500	1,14	11	55				62,70	
FS-2.1	1	1	16	B500	2,81	12	12					33,72
		2	12	B500	2,14	6	6				12,84	
		3	12	B500	1,14	11	11				12,54	
FS-2.2	1	1	12	B500	2,31	8	8				18,48	
		2	12	B500	1,44	14	14				20,16	
Podwalina BP-1 BP-2	1	1	12	B500	1096,48	1	1				1096,48	
		2	8	B500	2,32	374	374			867,68		
		3	6	B240	0,34	561	561	190,74				
Podwalina BP-1.3	1	1	12	B500	73,92	1	1				73,92	
		2	8	B500	2,12	26	26			55,12		
		3	6	B240	0,34	39	39	13,26				
RAZEM	[m]							204,00	1282,80	2169,96	202,32	
CIEŻAR 1mb	[kg/m]							0,22	0,4	0,89	1,58	
CIEŻAR ŁĄCZNY	[kg]							45,3	506,7	1926,9	319,7	
RAZEM STALI B220	[St0]											
RAZEM STALI B240	[St3S]							45,3				
RAZEM STALI B500	[RB500W LUB Bst500S]									2753,3		
OGÓŁEM										2798,6		